



TCP 24 Continuous-form Laser Printer



“Express Exchange Service”

Never down more than 24 hours!

www.taneum.com
1-800-829-7768

• **USPS MERLIN Compliant**

Intelligent Mail® Barcode Ready (4-State Customer Barcode)

The **TCP 24** Laser Printer features all of the versatility and print quality of a desktop laser printer without the top and bottom margin limitations.

High speed, high resolution, use of fanfold media, quick warm-up time, and quiet operation make it ideal for all PSL label applications, Tray and Bag Tags, Parcel Code 128 Labels, and Pallet Labels.

NO MORE MERLIN WORRIES!!!!!!

FEATURES:

- PRINT SPEEDS:

15,840 1-up Address Labels/hour

31,680 2-up Address Labels/hour

24 x 11" long pages per minute

- 300 dots / inch, print resolution
- Standard emulations include: PCL5e, Printronix VGL/PGL, Printronix IGP, Tally MT6xx, Line Printer Plus, Epson FX, IBM Proprinter
- Prints continuous tractor-feed media, up to 8.5" wide image area
- Small footprint: 18"w x 19"d x 10" h
- Reversible paper drive and leading edge, self-alignment reduces forms waste
- Straight-through paper path for worry-free forms handling
- Long life consumables for efficient operation
- Quiet Operation, < 53 dBA
- Ease-of-Serviceability is designed into printer to minimize downtime and lower service costs

TCP 24 Continuous Form, Laser Printer

Specifications

Speed: 24 pages per minute
(8.5" wide x 11" long)
15,840 1-up Address Labels/hour
31,680 2-up Address Labels/hour

Media Type: • 16-32 lb continuous fanfold media up to 9.5" wide (including tractor holes)
• Pressure Sensitive label stock (laser qualified); card stock; tag stock

Media Width: 4" to 9", tractor / pin feed

Print Width: 8.5", maximum

Media Length: 3" to 33" in 1/8" or 1/6" increments

Print Method: Electrophotography (diode laser)

Image Drum: OPC (Organic PhotoConductor)

Printing Resolution: 300x300 dots / inch

Fusing Method: Heat and Pressure

Electrical Requirements: 100-120/220-240 VAC
@ 50/60 Hz "Universal"
Peak amperage: 11 amps

Noise Level: **Operating:** <53 dBA

Operating Environment: • 50-90° F (10-32° C)
• 20-80% Relative Humidity, non-condensing

Dimensions: W 18" (456 mm)
D 19" (482 mm)
H 10" (254 mm)

Weight: 62 lb (28 kg)

User-Serviceable Items*

Toner - capacity 16,000 pages @ 4%
toner print density (black)
OPC Image Drum - 30,000 pages
Developer Unit - 100,000 pages

*Estimates based on 20 lb. bond, fanfold paper
(8.5" wide x 11" long) – other media may effect these estimates.

Emulations / Standard:

HP-LaserJet (PCL5e),
Printronix VGL/PGL, Printronix IGP,
Printronix Lineprinter Plus, Tally MT6xx,
IBM Proprinter, Epson FX,
MICROPLEX IDOL

Emulations / Optional:

IBM AFP / IPDS, IBM SCS,
QMS Code V, QMS Magnum,
Kyocera Prescribe,
Oasys Express, DEC LN03+, Tektronix
4010/4014, HPGL (7475 A), TIFF
(CCITT group 4), Bull MP6090, Fargo,
Datamax, Diablo 630, Xerox XES

Interfaces / Standard:

10 / 100 base-T Ethernet, USB,
RS232 Serial, IEEE 1284 and
Centronics Parallel

Interfaces / Optional:

Token Ring, Twin-ax, Co-ax

Monthly Duty Cycle:

50,000 pages
(8.5" wide by 11" long)

Optional Features:

Automated Stacker/Stand

Taneum Computer Products, Inc.

800 SW 34th Street - Suite D

Renton, WA 98057-4807

Phone: 1-800-829-7768 or 1-425-251-0711

Fax: 1-425-251-6332

www.taneum.com