

T2365 HD

Powerful & Rugged for Heavy Duty Operation



Tally

The T2365 HD and T2380 printers represent top of the line print speeds, rugged durability and unsurpassed performance under the most extreme conditions. These workhorse printers guarantee crisp, dark, clear and legible print thanks to the advanced engineering of the 24 pin print head. This head is built for long life and a heavy workload so even in the most challenging operating environment, you can be assured of the best in quality and performance.

Low running costs and durability in the harshest of print environments make these products excellent value for money.

- Up to 9 part forms
- Full range of automatic features to minimize user intervention
- Ideal for 'On-Demand' and 'Batch' applications with zero tear for no wasted forms
- Straight through paper path for easy forms loading
- Parallel and Ethernet (10/100BaseT) standard.
- Optional Interfaces: RS232 Serial; Coax/Twinax; Ethernet IPDS
- Straight through paper path for easy forms loading
- Compatible with a wide range of operating systems including Windows, UNIX, DOS, SAP R3 and legacy systems

These products are well matched to Microsoft Windows applications, and highly compatible with other host operation environments including legacy systems.

Fully automated operation, coupled with the 'straight through' paper path, allows ease of use and virtually eliminates errors caused by user intervention.

Available Configuration:

T2365- 2T
T2365 MC IGP with IGP/PJL Support

SERIAL MATRIX
PRINTERS

MOBILE
PRINTERS

THERMAL
PRINTERS

LINE MATRIX
PRINTERS

LASER
PRINTERS

CONNECTIVITY

CONSUMABLES

SERVICE

T2365 HD

Print Speed	At 10, 12 cpi: High Speed Draft 640, 800; Draft 533, 640; NLO 180, 215
Throughput	587 pages per hour (ECMA 132)
Character Density	5, 6, 7.5, 8.6, 10, 12, 15, 17.1, 20 cpi (Emulation dependent)
Line Density	2, 3, 4, 6, 8, 12 lpi
Printhead Life	500 million characters
Memory	128Kb
Standard Connectivity	Bi-directional parallel plus Ethernet 10/100BaseT with 128Kb buffer
Optional Connectivity	RS232 Serial, Adapters, Twinax/Coax, Ethernet IPDS
Standard Emulation	IBM® Proprinter, Epson® LQ (ESC P/2), Genicom ANSI, MTPL + Barcode/LCP IGP Version: IGP/PGL, Code V, MT660, Printronix, P6000,HP2564C
Optional Emulation	PCL3 (rugged writer)
Fonts	HS Draft, Draft, Copy Draft, Courier, Roman, Sans Serif, Prestige, Script, Orator, Gothic, Souvenir, Kix/Royal, OCR A, OCR B, 22 Bar Codes & scaleable LCP
Consumables	Ribbon: 20 million characters
STD Paper Handling	Push tractor with paper parking and AGA
Optional Paper Handling	2nd front tractor (user installable), paper pedestal, paper basket, paper cutting device
Paper Type	Continuous forms
Paper Weight	60-120gsm
Paper Size	100 to 420mm wide
Physical Weight	Approximately 42 lbs
Physical Size	(HxWxD): 11.0x24.6x17.0 inches
Power Voltage	AC 230V and 120V (selectable)
Power Consumption	60W printing
Workload	48,000 pages per month
Number of Copies	Up to 9 part forms
Temperature	+10° to +35°C
Humidity	20% to 80%
Acoustic	59dB(A)
Warranty	90 day on-site warranty

Note: For OCR applications it is recommended that your readers are tested with print samples supplied by DASCOM prior to purchase. Paper is a highly variable medium and should be tested prior to purchase. The quoted consumable life is the average for the printer when used under normal operating conditions.