



TANEUM 60

Continuous-Form Laser Printer



www.taneum.com

Phone: (800) 829-7768

• **USPS MERLIN Compliant**

Intelligent Mail® Barcode Ready (4-State Customer Barcode)

The **TCP 60** Laser Printer features all of the versatility and print quality of a desktop laser printer without the top and bottom margin limitations. Flash Fusion technology allows printing on virtually any stock.

High speed, high resolution, use of fanfold media, quick warm-up time, and quiet operation make it ideal for all Cheshire and PSL label applications.

NO MORE MERLIN WORRIES!!!!!!

FEATURES:

- **PRINT SPEEDS:**

118,800 Address Labels per hour!

45 11' pages per minute

2,970 lines per minute @ 6 lines / inch

3,960 lines per minute @ 8 lines / inch

- Xenon Flash Fusion technology offers the ability to print & fuse, using a variety of media
- 300 x 300 dots / inch, print resolution
- Standard emulations include PCL5e, PRINTRONIX IGP, Tally MT6xx, Line Printer Plus, Epson FX, IBM Pro-printer.
- Prints continuous tractor-feed media, up to 16" wide (adjustable from 6.5" to 16")
- Footprint:
31.7" (W) x 49.2" (H) x 33.5" (D)
805 mm (W) x 1250 mm (H) x 850 mm (D)
- Straight-through paper path for worry-free forms handling

TANEUM 60 Laser Printer

Specifications

Speed: 45 pages / minute (11" long)
59 pages / minute (8.5" long)
8.33 inches / second
3000 lines / minute @ 6 lines / inch

Media Type: 16-54 LB (Bond) continuous fanfold media
Pressure Sensitive label stock, card stock, tag stock, bond, plastics

Media Width: 6.5" to 16", tractor / pin feed

Print Width: 14.6", maximum

Media Length: 7" to 20" in 1/6" increments

Print Method: Electrophotography (LED Array)

Image Drum: Organic Photo Conductor (OPC) Drum

Printing Resolution: 300 x 300 dots / inch

Fusing Method: Flash fusion (Xenon bulb)

Input forms: Push Tractor

Output forms: Powered Stacker
3,000 pages (17 LB bond)

Keypad/Display: Graphic LCD Operator panel

Electrical Requirements: AC 200-240 V
@ 47-62 Hz, single phase
4.5 kVA (maximum), 0.3 kVA (Standby)

Noise Level: < 55 dBA (Standby)
< 65 dBA (Operating)

Operating Environment: 50-86° F (10-30° C)
30%-80% RH (non-condensing)

Dimensions: (W) 31.7" (805 mm)
(H) 49.2" (1250 mm)
(D) 33.5" (850 mm)

Weight: 529 LB (240 kg) with Stacker
485 LB (220 kg) printer only

Barcodes:

Linear: UPC A, UPC E, Code 39, Postnet, Planet Code, 4-State, EAN 8, EAN 8+ Add-on, EAN 128 (code 128), EAN 13, EAN 13+ Add-on, MSI, 2/5 2-stroke Datalogic, 2/5 3-stroke Matrix, 2/5 5-stroke Industry, Codabar, USD5, Kix and many more!

2-Dimensional: PDF 417, Datamatrix, Maxicode and many more!

Emulation / Standard:

HP-LaserJet (PCL5e),
Printronix IGP, Printronix Line Printer Plus, Tally MT6xx,
IBM Proprinter, Epson FX,
MICROPLEX IDOL

Emulations / Optional:

IBM AFP / IPDS, IBM SCS,
QMS Code V, QMS Magnum,
Kyocera Prescribe, Printronix VGL/PGL, Oasys Express, DEC LN03+,
Tektronix 4010/4014, HPGL (7475 A),
TIFF (CCITT group 4), Bull MP6090,
Fargo, Datamax, Diablo 630, Xerox XES

Interfaces / Standard:

10 / 100 base-T Ethernet, USB,
RS232 Serial, IEEE 1284 and
Centronics Parallel

Interfaces / Optional:

Token Ring, Twin-ax, Co-ax

Monthly Duty Cycle:

650,000 pages
(11" wide x 8.5" long, page format)
500,000 pages
(14 7/8" wide x 11" long, page format)

Included Features: Powered Drop Stacker
(No additional charge!)

Certifications: ANSI / UL 60950-1
CAN / CSA C22.2, No. 60950-1-03

Taneum Computer Products

P. O. Box 6178
Kent, WA 98064-6178
Phone: (800)829-7768
Fax: (425)251-6332

www.taneum.com