

FS-9520DN Specifications

BASIC SPECIFICATIONS:

Configuration:	Network Monochrome Printer with Standard 500 x 2 Drawers, Duplex unit, plus 200 Sheet Multi-Purpose Tray
Resolution:	Fast 1200 dpi (1800 x 600), 600 x 600 dpi, 2400 x 600 dpi (w/KIR)
Printer Memory:	Standard 64MB, upgradable to 576MB via 100 pin DIMMs, Optional HDD, Standard CF Card Slot (Type 1)
Electrical Requirements:	120V, 60Hz, 10.9A
Dimensions:	23"W x 25.2"D x 24.2"H
Weight:	147.9 lbs
Max Duty Cycle:	300,000 Pages Per Month

CONTROLLER SPECIFICATIONS:

Controller:	PowerPC750CX 500 MHz
Supported PDL / Emulations:	PRESCRIBE, PCL6 (PCL XL, PCL5e), KPDL3 (PS3), KCGL (HP-GL), Diablo 630, IBM ProPrinter X24, Epson LQ850, Line Printer
Fonts:	80 Outline Fonts for PCL XL/5e, 136 Outline fonts for KPDL3, 1 Bitmap Font
Windows™ OS Compatibility:	Windows™ 95/98/Me/NT4.x/2000/XP
Novell™ OS Compatibility:	Novell Network™ 3.x/4.x/5.x
Mac OS Compatibility:	OS 8.x/9.x/10.x
UNIX OS Compatibility:	Sun OS 4.1.x; Solaris 2.x; AIX; HP-UX (LPR)
Connectivity / Interface:	Standard 10/100BaseTX, Parallel IEEE1284, Hi-Speed USB 2.0, KU10 LV Expansion Slots (2):
	Optional Hard Drive Optional IB-20 10/100BaseTX, 10Base2; Optional IB-22 Enhanced Wireless NIC; Optional IB-11 RS232C Serial Interface
Supported Protocol:	TCP/IP, IPX/SPX, AppleTalk, NetBEUI
Driver:	KX Driver for Windows™, PPD for Mac, PPD for Linux/UNIX
Utilities:	KM-NET Viewer, KM-NET Remote Operation Panel, KM-NET Job Manager, KM-NET Printer Disk Manager, Network Advanced Setup Utilities, PRESCRIBE Utilities

OUTPUT SPEEDS:

Warm-Up Time:	Less than 25 Seconds
First Print Out:	Less than 5.0 Seconds
Pages Per Minute:	51 Letter, 26 Legal, 26 Ledger

PAPER SUPPLY:

Standard Paper Sources:	Dual 500 Sheet Drawers, 200 Sheet MPT
Drawer Paper Size:	5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17"
MPT Paper Size:	5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17", Custom (3.5" x 5.8" - 11.7" x 17.7")
Std/Max Paper Capacity:	1200 Sheets/4200 Sheets
Paper Weight:	16-28 lb Bond via Paper Drawers, 16 lb Bond - 110 lb Index via MPT
Input Materials:	Bond Paper, Recycled Paper, Transparencies, Labels, Envelopes

DUPLEX UNIT:

Paper Size:	5.5" x 8.5", 8.5" x 11", 11" x 17"
Paper Weight:	17 - 21 lb Bond

PAPER HANDLING OPTIONS:

DUAL PAPER DRAWERS: PF-70

Paper Capacity:	2 x 500 Sheets
Paper Weight:	16 - 28 lb Bond
Paper Size:	5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17"
Dimensions/Weight:	23.2"W x 12.4"D x 23.0"H/57.4 lbs

LARGE CAPACITY TRAY: PF-75

Paper Capacity:	3,000 Sheets
Paper Weight:	16 - 28 lb Bond
Paper Size:	8.5" x 11"
Dimensions / Weight:	23.2"W x 12.4"D x 23.0"H/48.0 lbs

FINISHER: DF-71

Stack Capacity:	3,000 sheets; Sub Tray: 250 Sheets
Paper Size:	Main Tray: 8.5" x 11" - 11" x 17"; Sub Tray: 5.5" x 8.5" - 11" x 17"
Paper Weight:	12 lb Bond - 110 lb Index
Staple Capacity:	50 Sheets: 8.5" x 11"; 30 Sheets: 8.5" x 14", 11" x 17"
Edge Staple Position:	3 Positions: Top Left, Bottom Left, Left/Top Side
Punch:	Standard 2 and 3 Hole
Dimensions / Weight:	27.1"W x 23.5"D x 41.5"H/110 lbs

SIMPLE FINISHER: DF-73

Stack Capacity:	Main Tray: 1,000
Paper Size:	Main: 8x5" x 11" - 11" x 17"; Sub: 5.5" x 8.5" - 11" x 17"
Paper Weight:	17 - 34 lb Bond
Staple Capacity:	30 Sheets: 8.5" x 11"; 20 Sheets: 8.5" x 14", 11" x 17"
Edge Staple Position:	1 Position: Top Left
Dimensions / Weight:	21.9"W x 23.5"D x 41.5"H / 110 lbs

SADDLE STITCH FINISHER: DF-75

Stack Capacity:	Main Tray: 1,000 Sheets
Paper Size:	Main: 5.5" x 8.5" - 11" x 17"
Paper Weight:	16 lb Bond - 110 lb Index
Staple Capacity:	50 Sheets: 8.5" x 11"; 25 Sheets: 8.5" x 14", 11" x 17"
Edge Staple Position:	4 Positions: Top Left, Bottom Left, Left Side, Center
Saddle Stitch:	8.5" x 11", 11" x 17"; Up to 10 Sheets
Punch Unit:	Optional 2 and 3 Hole
Dimensions / Weight:	28.3"W x 23.7"D x 39.4"H/86 lbs

PUNCH UNIT: PH-2

Paper Size:	8.5" x 11" - 11" x 17"
Paper Weight:	17 lb Bond - 110 lb Index
Number of Holes:	2 and 3
Weight:	5.2 lbs

MULTI-BIN MAILBOX: M-2107

Number of Trays:	7
Tray Capacity:	100 Sheets: 5.5" x 8.5", 8.5" x 11"; 50 Sheets: 8.5" x 14", 11" x 17"
Paper Weight:	17 - 21 lb Bond
Dimensions/Weight:	20.0"W x 15.7"D x 18.5"H / 22 lbs

OPTIONS:

HARD DISK DRIVE:

Enables Document Printing and e-MPS Functions; Private Print, Job Storage, Quick Copy, Proof & Hold, Virtual MailBoxes, Bar Code

ADDITIONAL OPTIONS:

Reversing Adapter for DF-75 (RA-1), Attachment Kit for DF-71 & DF-75 (AK-70P), Printer Stand

CONSUMABLES:

TK-70 Toner Container:	40,000 pages @ 5% Coverage*
	* Ships with 20,000 pages @ 5% Coverage



Specifications and design are subject to change without notice. All trademarks and registered trademarks are the property of their respective manufacturers.

Kyocera Mita America, Inc.
225 Sand Road, PO Box 40008,
Fairfield, NJ 07004-0008, USA
©2003 Kyocera Mita America, Inc.
www.kyoceramita.com

